



**NOTE:**

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
3. INSTALL METAL WORK TO SMACNA RECOMMENDATIONS.
4. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.
5. FLANGE OF METAL MUST BE FULLY SUPPORTED BY WOOD AND TERMINATED AT LEAST 1/2" (12.7 mm) FROM EDGE OF WOOD.
6. MINIMUM 2" (50.8 mm) WELD REQUIRED IN ALL DIRECTIONS OUT FROM ALL BREAKS IN METAL FLASHING.

**WARRANTY MEMBRANE REQUIREMENTS:**

**15-YEAR**

TPO - 45 MIL

**20-YEAR**

TPO - 60 MIL



**OUTSIDE CORNER WITH TPO COATED METAL (WITH BRAKE)  
INSTALLATION STEPS**

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION  
DATE:

04/16/2026

DETAIL NO.

**EZT-C-06A**

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE