



- NOTE:
1. REFER TO GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
 2. REFER TO EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
 3. INSTALL METAL WORK TO SMACNA RECOMMENDATIONS.
 4. FLANGE OF METAL MUST BE FULLY SUPPORTED BY WOOD AND TERMINATED AT LEAST 1/2" (12.7 mm) FROM EDGE OF WOOD.
 5. INSTALL APPROPRIATE TPO COATED METAL WITH 1/8" (3.175 mm) TO 1/4" (6.35 mm) MAX. BETWEEN ADJOINING SECTIONS.
 6. **SEE EZT-C-08A & EZT-C-08B FOR DETAILED INSTALLATION INSTRUCTIONS.**
 7. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.

WARRANTY MEMBRANE REQUIREMENTS:

15-YEAR
TPO - 45 MIL
20-YEAR
TPO - 60 MIL



INSIDE CORNER WITH TPO COATED METAL (WITH BRAKE)

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:
04/16/2026

NOT TO SCALE

DETAIL NO.

EZT-C-08