



**NOTE:**

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
3. T-JOINT COVER REQUIRED FOR 60 MIL MEMBRANE OR GREATER.
4. ANGLE CHANGE PATCH REQUIRED FOR ALL MEMBRANE THICKNESS.
5. EZ TPO NON-REINFORCED FLASHING (4" x 4" (101.6 mm x 101.6 mm) MIN. WITH ROUNDED CORNERS) MAY BE USED IN LIEU OF T-JOINT COVER.
6. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.

**WARRANTY MEMBRANE REQUIREMENTS:**  
**15-YEAR**  
 TPO - 45 MIL  
**20-YEAR**  
 TPO - 60 MIL

	<b>FLASHING LAP SPLICE WITH WELDED T-JOINT COVER AND ANGLE CHANGE PATCH</b>		MAXIMUM WARRANTY: 20 Years	
	MATERIAL: EZ TPO	ACCEPTABLE SYSTEMS: ALL	ISSUE / REVISION DATE: <b>04/20/2026</b>	DETAIL NO. <b>EZT-LS-12</b>
GENFLEX: (800) 443-4272 www.genflex.com			NOT TO SCALE	