



NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
2. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.
3. MINIMUM FOUR (4) PLATES AND FASTENERS REQUIRED. FOR PENETRATIONS GREATER THAN 8" IN DIAMETER, INSTALL PLATES AND FASTENERS AT A MINIMUM OF 12" (304.8 mm) ON CENTER AROUND PENETRATION BASE.

EZ TPO MEMBRANE TARGET PATCH

GENFAST FASTENER AND 2 3/8" OR 3" MAX SEAM PLATE (SEE NOTE #3)

WELDED SPLICE 2" (50.8 mm) MIN.

OUTSIDE EDGE OF PENETRATION FLASHING

EZ TPO FIELD MEMBRANE

WARRANTY MEMBRANE REQUIREMENTS:
15-YEAR
 TPO - 45 MIL
20-YEAR
 TPO - 60 MIL



MEMBRANE SECUREMENT AT PENETRATION WITH SEAM PLATES AND TARGET PATCH

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

04/20/2026

DETAIL NO.

EZT-P-15

NOT TO SCALE

GENFLEX: (800) 443-4272 www.genflex.com