



NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
3. METAL ANCHOR BAR MAY BE USED IN LIEU OF SEAM PLATES.
4. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.
5. MINIMUM FOUR (4) PLATES AND FASTENERS REQUIRED. FOR PENETRATIONS GREATER THAN 8" IN DIAMETER, INSTALL PLATES AND FASTENERS AT A MINIMUM OF 12" (304.8 mm) ON CENTER AROUND PENETRATION BASE.

8" (203.2 mm) WIDE TPO COVER STRIP WELDED TO TPO FIELD MEMBRANE (SEE NOTE #2 & #4).

OUTSIDE EDGE OF PENETRATION FLASHING

GENFAST FASTENER AND 2 3/8" OR 3" MAX SEAM PLATE (SEE NOTE #3, #5)

EZ TPO FIELD MEMBRANE

WARRANTY MEMBRANE REQUIREMENTS:
15-YEAR
TPO - 45 MIL
20-YEAR
TPO - 60 MIL



MEMBRANE SECUREMENT AT PENETRATION WITH SEAM PLATES AND 8" COVER STRIPS

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:
04/20/2026

DETAIL NO.
EZT-P-16

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE