



- NOTE:
1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
  2. STEP #1 - APPLY CONTINUOUS BEAD OF GENFLEX WATER STOP CENTERED UNDER FASTENERS. ROUND ALL METAL CORNERS AND FASTEN METAL SCUPPER WITH APPROPRIATE FASTENERS.
  3. STEP #2 - STRIP IN CORNERS OF SCUPPER WITH PRE-MOLDED EZ TPO INSIDE / OUTSIDE CORNERS. EZ TPO NON-REINFORCED FLASHING MAY BE USED IN LIEU OF PRE-MOLDED CORNERS.

**USE APPROPRIATE BASE TIE-IN DETAIL**

**WARRANTY MEMBRANE REQUIREMENTS:**  
**15-YEAR**  
 TPO - 45 MIL  
**20-YEAR**  
 TPO - 60 MIL

|   |  |                         |  |                                |
|---|--|-------------------------|--|--------------------------------|
|   | <b>OVERFLOW THRU-WALL SCUPPER WITH EZ TPO COATED METAL<br/>         INSTALLATION INSTRUCTION STEPS 1 &amp; 2</b> |                         | MAXIMUM WARRANTY: 20 Years                     |                                |
|   | MATERIAL: EZ TPO   | ACCEPTABLE SYSTEMS: ALL | ISSUE / REVISION<br>DATE:<br><b>04/20/2026</b> | DETAIL NO.<br><b>EZT-S-06A</b> |
| GENFLEX: (800) 443-4272 www.genflex.com |  |                         | NOT TO SCALE                                   |                                |