



- NOTE:
1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
  2. REFER TO DETAIL EZT-FB-LS-01 OR EZT-FB-LS-03 FOR WELD WIDTH.
  3. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES.
  4. REFER TO EZT-FB-BT-09 & EZT-FB-BT-10 FOR MEMBRANE SECUREMENT AT CORNERS.
  5. MEMBRANE ADHESIVE REQUIRED BETWEEN MEMBRANE AND INSULATION FOR ADHERED SYSTEMS.
  6. WHEN REINFORCEMENT OF MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.
  7. REFER TO GENFLEX PDS SHEETS AND EZ TPO GUIDES FOR LIST OF COMPATIBLE SUBSTRATES AND APPLICABLE ATTACHMENT METHODS.

**WARRANTY MEMBRANE REQUIREMENTS:**  
**15-YEAR**  
 TPO - 45 MIL  
**20-YEAR**  
 TPO - 60 MIL



**BASE TIE-IN AT CURB / PARAPET WITH EXISTING CANT**

MATERIAL: EZ FLEECE BACKED TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:  
 04/20/2026

DETAIL NO.  
 EZT-FB-BT-03

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE