



**NOTE:**

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-FB-LS-01 OR EZT-FB-LS-03 FOR WELD WIDTH.
3. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.
4. GENFLEX QUICK DUAL MAY BE APPLIED IN SPATTER PATTERN AT 60-70% COVERAGE IN THE FIELD AND 75-85% COVERAGE AT THE BASE TIE-IN.
5. MECHANICAL FASTENING OF THE BASE TIE-IN REQUIRED WHEN ANY OF THE FOLLOWING CONDITIONS APPLY:
  - WARRANTIES GREATER THAN 20-YEARS
  - WIND SPEED COVERAGE 90 MPH OR GREATER
  - EXPANSION OR CONTROL JOINTS OR LOCATIONS WITH EXPECTED BUILDING MOVEMENT.

**WARRANTY MEMBRANE REQUIREMENTS:**

**15-YEAR**  
TPO - 45 MIL  
**20-YEAR**  
TPO - 60 MIL



**BASE TIE-IN WITH FOAM ADHESIVE  
AND SEPARATE EZ TPO FLASHING**

MATERIAL: EZ FLEECE BACKED TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION  
DATE:

04/20/2026

DETAIL NO.

EZT-FB-BT-12

NOT TO SCALE

GENFLEX: (800) 443-4272 www.genflex.com