

STEP #1

APPROPRIATE EZ TPO COATED METAL (SEE NOTE #2)

1-1/4" (32 mm) HOT DIPPED GALVANIZED ROOF NAILS @ 4" (102 mm) O.C. MAX.

APPROPRIATE INSULATION
SUBSTRATE

WALL

1/8" (3 mm) MIN. TO 1/4" (6 mm) MAX.

CONTINUOUS CLEAT (BY OTHERS)

NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
2. INSTALL METAL WORK TO SMACNA RECOMMENDATIONS.
3. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES.

STEP #2

HEAT RESISTANT TAPE (BY OTHERS) OVER EZ TPO COATED METAL SPLICE

APPROPRIATE INSULATION
SUBSTRATE

WALL

WOOD NAILER (SEE NOTE #3)

WARRANTY MEMBRANE REQUIREMENTS:

15-YEAR
TPO - 45 MIL
20-YEAR
TPO - 60 MIL



ROOF EDGE WITH EZ TPO COATED METAL WITH EZ FB TPO MEMBRANE SELVEDGE EDGE AT SPLICE - INSTALLATION STEPS 1 & 2

MATERIAL: EZ FLEECE BACKED TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:
04/20/2026

DETAIL NO.

EZT-FB-RE-05A

NOT TO SCALE

GENFLEX: (800) 443-4272 www.genflex.com