



- NOTE:
1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
 2. REFER TO DETAIL EZT-PS-LS-01 OR EZT-PS-LS-02 FOR WELD WIDTH.
 3. REFER TO EZT-PS-BT-16 & EZT-PS-BT-17 FOR MEMBRANE SECUREMENT AT CORNERS.
 4. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EXT-PS-LS-04 FOR CUT EDGE SEALANT APPLICATION.
 5. REFER TO GENFLEX TIS SHEETS AND APPLICATION GUIDES FOR LIST OF COMPATIBLE SUBSTRATES WITH EZ TPO PEEL & STICK MEMBRANE.
 6. STANDARD EZ TPO MEMBRANE WITH APPROPRIATE MEMBRANE ADHESIVE OR EZ TPO PEEL & STICK MEMBRANE MAY BE USED AS WALL FLASHING.
 7. APPROPRIATE PRIMERS INCLUDE GENFLEX CLEAR PRIMER AND GENFLEX CLEAR LVOC PRIMER.
 8. APPROVED PRIMER REQUIRED ON ALL VERTICAL SURFACES.

	BASE TIE-N WITH GENFAST FASTENER AND PLATE FASTENED TO WALL/CURB		MAXIMUM WARRANTY: 20 Years	
	MATERIAL: EZ TPO P&S	ACCEPTABLE SYSTEMS: ADHERED	ISSUE / REVISION DATE: 04/20/2026	DETAIL NO. EZT-PS-BT-02
GENFLEX: (800) 443-4272 www.genflex.com			NOT TO SCALE	