



USE APPROPRIATE BASE TIE-IN

NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. WATER TIGHT INTEGRITY OF THE WALL AND COPING MUST BE MAINTAINED BY OTHERS.
3. COPING STONE ATTACHMENT IS THE RESPONSIBILITY OF THE SPECIFIER.
4. ANCHOR BOLT SECUREMENT LUG MUST BE INSTALLED IN ACCORDANCE WITH MASONRY STANDARDS AND LOCAL BUILDING CODES.
5. GENFLEX EZ TPO PEEL & STICK MEMBRANE EXTENDING TO FACE OF WALL.
6. CONTINUOUS BEAD OF GENFLEX WATERSTOP ALONG ENTIRE EDGE OF TPO AND WALL. WATERSTOP ALSO APPLIED AROUND ANCHOR.
7. GENFLEX EZ TPO PEEL & STICK CAN BE USED AS VERTICAL WALL FLASHING.
8. APPROVED PRIMER REQUIRED ON ALL VERTICAL SURFACES WHEN EZ TPO PEEL & STICK IS USED FOR FLASHING.
9. REFER TO TPO APPLICATION GUIDE FOR ACCEPTABLE FLASHING SUBSTRATES
10. IF INTERMEDIATE ATTACHMENT IS REQUIRED, COMPLETE AS FOLLOWS:
 - UP TO 5' (1.52 m) WALL HEIGHT- NONE REQUIRED
 - 5' (1.52 m) - 10' (3.05 m) WALL HEIGHT - ONE ATTACHMENT AT 1/2 THE WALL HEIGHT
 - ABOVE 10' (3.05 m) - ONE ATTACHMENT EVERY 3' (0.91 m)



TERMINATION AT TOP OF WALL WITH COPING STONE

MATERIAL: EZ TPO P&S

ACCEPTABLE SYSTEMS: ADHERED

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

04/20/2026

DETAIL NO.

EZT-PS-T-02

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE