



NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
2. ALLOW 1/4" (6.35 mm) MAX. SPACE BETWEEN SECTIONS OF DRAIN BAR.
3. DO NOT PRE-NAIL MEMBRANE TO THE FACE OF THE WOOD NAILER.
4. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES.
5. IF METAL COUNTER-FLASHING EXCEEDS 4" (101.6 mm) IN WIDTH, A CONTINUOUS CLEAT MUST BE INSTALLED.
6. ON BALLASTED ROOFS, DRAIN BAR HEIGHT MUST MEET OR EXCEED BALLAST OR PAVER HEIGHT (2" (50.8 mm) MIN. ABOVE ROOF SURFACE).
7. GENFLEX TERMINATION BAR AND STAINLESS STEEL FASTENERS MAY BE USED IN LIEU OF METAL DRAIN BAR FOR MECHANICALLY ATTACHED AND ADHERED SYSTEMS ONLY.

WARRANTY MEMBRANE REQUIREMENTS:
15-YEAR
TPO - 45 MIL
20-YEAR
TPO - 60 MIL



**EZ TPO ROOF EDGE WITH METAL BAR TERMINATION
(DRAIN BAR OR TERMINATION BAR)**

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:

04/20/2026

DETAIL NO.

EZT-RE-18

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE