



NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
2. ALLOW 1/4" (6.35 MM) MAX. SPACE BETWEEN SECTIONS OF DRAIN BAR.
3. DO NOT PRE-NAIL MEMBRANE TO THE FACE OF THE WOOD NAILER.
4. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES.
5. IF METAL COUNTER-FLASHING EXCEEDS 4" (101.6 mm) IN HEIGHT, A CONTINUOUS CLEAT MUST BE INSTALLED.
6. ON BALLASTED ROOFS, DRAIN BAR HEIGHT MUST MEET OR EXCEED BALLAST PAVER HEIGHT (2" (50.8 mm) MIN. ABOVE ROOF SURFACE).

WARRANTY MEMBRANE REQUIREMENTS:

15-YEAR
TPO - 45 MIL
20-YEAR
TPO - 60 MIL



EZ TPO ROOF EDGE WITH SLOTTED DRAIN BAR (BY OTHERS)

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

04/20/2026

DETAIL NO.

EZT-RE-19

NOT TO SCALE