



WALL SYSTEM MUST BE WATERPROOFED AND MAINTAINED IN ORDER FOR ANY SURFACE MOUNTED TERMINATION TO BE EFFECTIVE

WARRANTY MEMBRANE REQUIREMENTS:
15-YEAR
 TPO - 45 MIL
20-YEAR
 TPO - 60 MIL

- NOTE:
1. REFER TO GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
 2. REGULAR MAINTENANCE OF COUNTER-FLASHING AND SEALANTS REQUIRED. NOT INCLUDED AS PART OF THE ROOFING SYSTEM LIMITED WARRANTY.
 3. METAL COUNTER-FLASHING SHALL BE 24 GAUGE PRE-FINISHED STEEL OR .032" (8 mm) MIN. ALUMINUM FORMED WITH HEMMED LOWER EDGE.
 4. INSTALL METAL WORK IN ACCORDANCE WITH CURRENT SMACNA RECOMMENDATIONS.
 5. IT IS IMPORTANT THAT THE SELF ADHERED WATERPROOFING MEMBRANE NOT TOUCH THE GENFLEX TPO MEMBRANE.



TERMINATION AT EIFS OR WALL CLADDING	
MATERIAL: EZ TPO	ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years	
ISSUE / REVISION DATE:	DETAIL NO.
04/20/2026	EZT-T-07
NOT TO SCALE	