



**NOTE:**

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
3. NAILING AND METAL COUNTER-FLASHING ARE NOT REQUIRED IF MEMBRANE EXTENDS UP AND OVER CURB WALLS PRIOR TO INSTALLATION OF R.T.U.
4. METAL COUNTER-FLASHING SHALL BE 24 GAUGE PRE-FINISHED STEEL OR .032" (0.81 mm) MIN. ALUMINUM FORMED WITH HEMMED LOWER EDGE MOUNTED TIGHTLY TO UNDERSIDE OF MECHANICAL UNIT.
5. MAXIMUM 10" (254 mm) LONG FASTENERS. (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENT).
6. APPROPRIATE GENFLEX MEMBRANE ADHESIVE REQUIRED BETWEEN MEMBRANE AND INSULATION FOR ADHERED SYSTEMS.
7. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.
8. INSTALL METAL WORK IN ACCORDANCE WITH CURRENT SMACNA RECOMMENDATIONS.

**WARRANTY MEMBRANE REQUIREMENTS:**  
**15-YEAR**  
 TPO - 45 MIL  
**20-YEAR**  
 TPO - 60 MIL



**TERMINATION AT R.T.U. WITH COUNTER-FLASHING  
 AND SEPARATE FLASHING (UNIT FLANGE MOUNTED TO SUBSTRATE)**

|                  |                         |
|------------------|-------------------------|
| MATERIAL: EZ TPO | ACCEPTABLE SYSTEMS: ALL |
|------------------|-------------------------|

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:  
 04/20/2026

DETAIL NO.  
**EZT-T-19**

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE