

WARRANTY MEMBRANE REQUIREMENTS:

UP TO 15-YEAR: 45 mil

UP TO 20-YEAR: 60 mil

**USE APPROPRIATE
TERMINATION**

3/4" (19.05 mm) TO 1" (25.4 mm)

WALL / CURB

USE APPROPRIATE GENFLEX
MEMBRANE ADHESIVEPEEL & STICK RPS STRIP MUST EXTEND
1/2" (12.7 mm) ABOVE BAR ANCHOR STRIPGENFLEX BAR ANCHOR FASTENED @ 12" (304.8 mm) O.C.
MAX. WITH GENFLEX FASTENERS AND TERMINATION
CAULK OVER FASTENER HEADS (SEE NOTE #3 & #5)

PEEL & STICK RPS STRIP (SEE NOTE #2)

ACCEPTABLE GENFLEX PRIMER

APPROPRIATE GENFLEX EPDM MEMBRANE

USE APPROPRIATE GENFLEX
MEMBRANE ADHESIVE (SEE NOTE #4)

INSULATION

SUBSTRATE

NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
2. REFER TO DETAIL BT-14 AND BT-15 FOR PEEL & STICK RPS STRIP LAYOUT AT CORNERS.
3. POLYMER BATTEN STRIP OR BAR ANCHOR ACCEPTABLE FOR WOOD OR METAL SUBSTRATE. BAR ANCHOR MUST BE USED WITH MASONRY SUBSTRATE.
4. MEMBRANE ADHESIVE REQUIRED BETWEEN MEMBRANE AND INSULATION FOR FULLY ADHERED SYSTEM.
5. BAR ANCHOR REQUIRED FOR 20 YEAR WARRANTIES.

**BASE TIE-IN WITH PEEL & STICK RPS
AND BAR ANCHOR FASTENED TO WALL OR CURB**

MATERIAL: EPDM

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: SEE TABLE

ISSUE / REVISION
DATE:

04/30/2026

DETAIL NO.

BT-04

NOT TO SCALE

GENFLEX: (800) 443-4272 www.genflex.com