


Submittal Sheet

EZ TPO Attached Membrane Steel Deck

Roofing System Limited Warranty:
Up to 20 Years, 55 mph



- GenFlex™ EZ TPO Membrane
- Mechanically Attached with Appropriate Fastening System
- Cover Board (Optional) – Mechanically Attached or Adhered
- Insulation – Mechanically Attached or Adhered
- Steel Deck

Slope Requirement:

Positive drainage required for warranty.

Construction Type:

☐ New Construction ☐ Complete Tear-off ☐ Recover (Any wet or damaged materials removed prior to installation)

Building Height Limitation:

GenFlex EZ TPO Mechanically Attached Systems are limited to buildings 120' (36.6 m) or less.

Air Barrier:

An air barrier is recommended for projects with large wall openings greater than 10% of the total wall area.

Vapor Barrier:

☐ GenFlex Vapor Shield ☐ 4-6 mil poly ☐ Thermal Barrier

*Thermal barrier required when using Vapor Shield over a Steel Deck on FM Insured or FM Specified projects.

Base Tie-Ins:

Must be attached to substrates which provide a minimum of 200 lbf (1 kN) in any direction.

Increased Wind Speed and Codes:

Any wind speed coverage exceeding 55 mph (88 km/h) or projects with code requirements must be reviewed by a GenFlex Regional Technical Coordinator.

Deck Requirement:

☐ Minimum 22 Gauge Steel

Insulation Fasteners and Plates:

☐ GenFast™ #12 Fastener and GenFlex 3" Insulation Plates ☐ GenFast #14 Fastener and GenFlex 3" Insulation Plates
☐ GenFast #12 Preassembled Screw and Plate ☐ GenFast #14 Preassembled Screw and Plate

Membrane Requirement:

☐ GenFlex EZ TPO Membrane, 45 mil (max 15 year) ☐ GenFlex EZ TPO Membrane, 60 mil
☐ GenFlex EZ TPO Plus Membrane, 80 mil

Membrane Attachment (Row Spacing):

☐ Max 15-Year Warranty, Any Thickness, Maximum 12' Row Spacing, Fasteners Spaced Maximum 12" o.c.
☐ 20-Year Warranty, EZ TPO (45 mil), Maximum 8' Row Spacing, Fasteners Spaced Maximum 6" o.c.
☐ 20-Year Warranty, EZ TPO (min. 60 mil), Maximum 12' Row Spacing, Fasteners Spaced Maximum 12" o.c.

Membrane Fasteners and Plates:

☐ GenFast #15 WH Fastener and GenFast 2 3/8" WH Seam Plate
☐ GenFast #16 MAX Fastener and GenFast 3" MAX Seam Plate

Seaming Requirement:

1.5" Single Weld System (use robot welder). Joint covers are required at all joints and at angle changes 1:12 or greater.

GenFlex Factory Formed Edge Metal System:

☐ GenFlex Coping System ☐ GenFlex Fascia System
☐ GenFlex Drip Edge ☐ GenFlex TPO Skirted Drip Edge

Non-Factory Formed Edge Conditions:

☐ GenFast Termination Bar ☐ GenFlex TPO Coated Metal ☐ GenFlex Approved Detail

Substrate Attachment Rates for Standard 55 mph Wind Speed (Top Layer, 4' x 8' Board)

Thickness	Substrate Material	Minimum Fasteners
☐ 1.0" – 1.4"	☐ GenFlex GL ISO or GenFlex ISO or ☐ GenFlex CG ISO or Coated Glass Facer Polyiso	5
☐ 1.5" – 1.9"		5
☐ 2.0" – 4.0"		5
☐ 1.5" – 1.9"	☐ GenFlex NB ISO or NailBase Composite Board / ☐ OSB / ☐ Plywood (Plate and Fastener)	5
☐ 2.0" – 4.0"		5
☐ GenFlex NB ISO or NailBase Composite Board / OSB / Plywood		5
☐ GenFlex HD Composite ISO		5
☐ GenFlex HD ISO or GenFlex ½" HD ISO Cover Board		5
☐ 1/4"	☐ SECUROCK® Gypsum-Fiber Roof Board ☐ SECUROCK UltraLight Coated Glass-Mat Roof Board	5
☐ 1/2"		5
☐ 5/8"		5
☐ 1/4"	SECUROCK UltraLight Glass-Mat Roof Board NOTE: Not for use with adhered membrane or insulation adhesives. May be used as insulation layer or thermal barrier layer when fastened through.	5
☐ 1/2"		5
☐ 5/8"		5
☐ 1/2"	SECUROCK Cement Roof Board	5
☐ 5/8"		5
☐ 1/4"	DensDeck® Prime Roof Board	5
☐ 1/2"		5
☐ 5/8"		5
☐ 5/8"	DensDeck Prime StormX™ Roof Board	5
☐ 1/4"	DEXcell® Glass Mat Roof Board NOTE: Not for use with adhered membrane or insulation adhesives. May be used as insulation layer or thermal barrier layer when fastened through.	5
☐ 1/2"		5
☐ 5/8"		5
☐ 1/4"	DEXcell FA™ Glass Mat Roof Board	5
☐ 1/2"		5
☐ 5/8"		5
☐ 7/16"	DEXcell Cement Roof Board	5
☐ 5/8"		5
☐ 5/8"	DEXcell FA VSH™ Glass Mat Roof Board	5
☐ 1/2"	Structodek® High Density Wood Fiber Board	5
☐ 1/2"	Alleguard Fanfold Rigid Board Insulation (max. 20-year warranty, Re-Cover only)	5 per 32 sq. ft.
NOTE: 1. Only GenFlex brand products are covered in a GenFlex Roof System Warranty. 2. Refer to the GenFlex Technical Database at www.genflex.com for additional information regarding appropriate roof systems and roof system warranty requirements. Review appropriate details and installation requirements based on warranty term requested. 3. It is the installing contractor's responsibility to follow all applicable building codes. 4. Contact GenFlex Technical Services for full warranty requirements. 5. DensDeck is a registered trademark of Georgia-Pacific Gypsum LLC, SECUROCK is a registered trademark of USG Corporation, Structodek is a registered trademark of Blue Ridge Fiberboard, Inc., and DEXcell is a registered trademark of National Gypsum Company. of National Gypsum Company.		

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.