Product Data Sheet



FlexWhite™ Peel & Stick EPDM Flashing

Item Description	Item Number
12" x 25' (304.8 mm x 7.6 m)	W590030199
*1 roll per carton	
NOTE: Each package contains GenFlex Scrub Pads and Handles	

Description

GenFlex FlexWhite Peel & Stick EPDM Flashing is a semi-cured white EPDM flashing laminated to a cured tape. FlexWhite Peel & stick EPDM flashing is specifically designed to be used in FlexWhite EPDM and TPO roofing applications for flashing pipes and other field fabricated flashing details.

Method of Application

Refer to current GenFlex Technical Specifications for additional application instructions.
IMPORTANT: Ensure both mating surfaces are free of debris and no moisture is present on the splicing surfaces.

1. Thoroughly mix GenFlex FlexWhite Clear Primer. **DO NOT THIN!** A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. Clean all surfaces with a clean cotton rag removing excess dirt or contamination prior to application of the primer.
3. With a GenFlex scrub pad and handle, apply GenFlex FlexWhite Clear Primer using long and continuous back and forth strokes with heavy to moderate pressure along the bonding area until no streaks or puddling occurs.
4. Allow GenFlex FlexWhite Clear Primer to dry until slightly tacky to a dry finger touch.
5. Cut the FlexWhite Peel & Stick Flashing to the desired size to fit the specific detail.
6. Peel off the release paper from the flashing and apply it to the primed area. Use care not to over stretch or thin out the flashing material.
7. Using Teflon coated or hard rubber roller, hand-roll the flashing firmly to ensure uniform contact. Pay special attention to any factory seam step downs and field seam intersections.
8. Apply a continuous “high profile” bead of FlexWhite Edge Caulk to the entire edge of the FlexWhite Flashing per current GenFlex Technical specifications.

Storage

- Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life.
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life

Shelf Life of 6 months. Shelf life will be shortened if exposed to elevated temperatures.

LEED® Information

Post-Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Precautions

- To avoid sources of punctures and physical damage, take care when moving, transporting, or handling, etc. to avoid sources of punctures and physical damage.
- Contact GenFlex Roofing Systems Technical Department for specific recommendations.
- FlexWhite Peel & Stick EPDM Flashing is semi-cured. Do not stretch.
- Refer to Safety Data Sheet for additional information.

Typical Properties

EPDM	Typical Value	Tape	Typical Value
Color	White	Color	White
Base	EPDM	Base	Rubber Polymer
Solids	100%	Solids	100%
Cure State	Semi-cured	Cured State	Cured
Thickness	0.06" (1.5 mm) ± 10%	Thickness	0.025" ± 0.007" (0.625 mm ± 0.18 mm)

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.