Product Data Sheet



FlexWhite™ Clear Primer

Item Description	Item Number
3-gallon (11.4 liter)	W590030118

Description

GenFlex FlexWhite Clear Primer is an adhesion promoter designed to clean and prime GenFlex FlexWhite EPDM or TPO membranes prior to application of FlexWhite Peel & Stick™ accessories, FlexWhite Clear Primer must be applied with a Scrub Pad and Handle.

Method of Application

Refer to current GenFlex Technical Specifications for additional instructions.

IMPORTANT: Ensure the receiving surfaces are free of debris and no moisture is present.

1. Thoroughly mix GenFlex Clear Primer. DO NOT THIN! A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. Clean all surfaces with a clean cotton rag and Cleaner, removing excess contamination prior to application of the primer.
3. With a scrub pad and handle, apply GenFlex Clear Primer, using long and continuous back and forth strokes with heavy to moderate pressure, along the bonding area until no streaks or puddling occurs.
4. Allow GenFlex Clear Primer to dry until slightly tacky to a dry finger touch.
5. Proceed with application of Peel & Stick accessory as required by current product specifications.

Storage

- Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life.
- Do not store on roof in direct sunlight.
- When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life

12 months; shelf life will be shortened if exposed to elevated temperatures.

Precautions

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

- Open all doors and windows.
- Close containers after use.
- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.
- Avoid prolonged and repeated contact with skin. Keep out of reach of children.
- Keep away from your eyes.
- Use chemically resistant gloves.
- Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

V.O.C. Content: 640 g/L

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties

Property	Typical Value
Base	Synthetic Polymers
Color	Clear-Translucent Light Yellow
Solids	15 ± 2%
Viscosity	Free flowing, easy to apply
Weight	6.5 ± 0.1 lb/gal (0.8 ± 0.1 kg/L)
Specific Gravity	0.78 ± 0.01
Flash Point	10 °F (-12 °C)

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.